



新榮科技 公司

SUN WING TECHNOLOGY COMPANY

九龍塘尾道 54-58 號永利工業大廈二樓 205 室  
Room 205, 2/F, Wing Lee Ind. Bldg, 54-58, Tong Mei Rd., Kln, HK  
Tel: 2396 2884, 2332 8806 Fax: 2787 4865

E-mail: [sunwingt@netvigator.com](mailto:sunwingt@netvigator.com) Web Site: <http://www.sunwingtechnology.com>

## PLATINUM COATED ANODES

Plating coated anodes is suitable for gold and rhodium plating in industrial and decorative applications. It can be also applied in copper/nickel/chrome plating.

Specifications:

Standard sizes: up to 30"x60".

Coating thicknesses: from 1 to 5 microinches.

Current density and voltage can be operated up to 150 ASF and 8 volt respectively in most plating solutions.

Available in expanded mesh or solid sheet.

Anodes designed for special operating conditions and customized applications where conforming anodes are required.

## 白金鈦網陽極

用途：

適用於裝飾性鍍金和鍍鉑，亦可用於鍍鉻、鎳、鉻電鍍

規格及特性：

有數種標準規格，最大尺寸可至 30"x60"

白金厚度由 1-5 微米，以 2.5 微米最適用

操作電流密度可達至 15dm<sup>2</sup>，電壓至 8Volts

陽極網可根據客戶要求而製作

